



FESTO Valve VOFC

Characteristics

Series: VOFC

Operation: Electrical

Operating temperature: -25 / 60 °C

Fluid: Compressed air in accordance with ISO8573-1:2010 [7:4:4]

Flow rate at 6 Bar l/min	Port thread type	Port Size in	Operating pressure bar	Function	Pilot supply	Construction size	Protection class	Housing material	Seal material	Article
1.03			2.5 / 8	5/2 monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163699
1.03			2.5 / 8	5/2 monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163698
1.03			2.5 / 8	5/2 monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163697
1.03			2.5 / 8	5/2 monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163696
2.686		1/2	2 / 8	3/2 closed, monostable	Internal	12	IP65	Aluminium Ematal coated	NBR	14163585
2.686		1/2	2 / 8	3/2 closed, monostable	Internal	12	IP65	Aluminium Ematal coated	NBR	14163584
2.686		1/2	2 / 8	3/2 closed, monostable	Internal	12	IP65	Aluminium Ematal coated	NBR	13624240
2.686		1/2	2 / 8	3/2 closed, monostable	Internal	12	IP65	Aluminium Ematal coated	NBR	14163588
2.686		1/2	2 / 8	3/2 closed, monostable	Internal	12	IP65	Aluminium Ematal coated	NBR	14163587
766			1 / 8	3/2 closed, monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	13275313
766			1 / 8	3/2 closed, monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	13401122
766			1 / 8	3/2 closed, monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163578
766			1 / 8	3/2 closed, monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163582
766			1 / 8	3/2 closed, monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163581
766	BSPP (G)	1/4	0 / 8	3/2 closed, monostable	Internal		IP65			13531588
766	NPT	1/4-18	1 / 8	3/2 closed, monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163577
766	NPT	1/4-18	1 / 8	3/2 closed, monostable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163576
989			2.5 / 8	5/2 Bistable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163700
989			2.5 / 8	5/2 Bistable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163702
989			2.5 / 8	5/2 Bistable	Internal	6	IP65	Aluminium Ematal coated	NBR	14163701
										13446637
										14163586

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.