



FESTO Swivel/gripper unit HGDS

Characteristics

Series: HGDS

Operating temperature: 5 / 60 °C

Manufacturer ID	Bore diameter mm	Operation	Stroke length mm	Connection	Total force at 6 bar, closing N	Total force at 6 bar, opening N	Operating pressure bar	Article
HGDS-PP-12-P1-A-B	12	Double acting	2.5	M5	74	84	3 / 8	14171236
HGDS-PP-12-YSRT-A-B	12	Double acting	2.5	M5	74	84	3 / 8	14171239
HGDS-PP-12-P-A-B	12	Double acting	2.5	M5	74	84	3 / 8	14171234
HGDS-PP-16-P1-A-B	16	Double acting	4.5	M5	102	116	3 / 8	14171238
HGDS-PP-16-YSRT-A-B	16	Double acting	4.5	M5	102	116	3 / 8	14171240
HGDS-PP-16-P-A-B	16	Double acting	4.5	M5	102	116	3 / 8	14171237
HGDS-PP-20-P1-A-B	20	Double acting	7	M5	168	192	3 / 8	14171241
HGDS-PP-20-YSRT-A-B	20	Double acting	7	M5	168	192	3 / 8	14171242
HGDS-PP-20-P-A-B	20	Double acting	7	M5	168	192	3 / 8	12317676

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.