

ECON® Butterfly valve Type: 5821 Ductile cast iron/Aluminum bronze Squeeze handle Lug type



Characteristics

Type: 5821
Norm: EN (DIN)
Valve design: Centric
Housing material: Ductile cast iron
Material quality: EN-JS1030
Surface protection: Paint min. 60 µm
Connection: Lug type
Standard connection: EN (DIN)
Face to Face norm: EN 558, Series 20

Characteristics [2]

Operation: Squeeze handle
Top flange standard: ISO 5211 Direct Mount
Housing lining: Vulcanized
Disk material: Aluminum bronze
Quality class disc: CC333G
Actuator material: EN-JS1030

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length	Material liner	Spindle material	Quality class spindle	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Article
			mm				°C	°C	
DN50	PN16	PN10/16	43	NBR	Stainless steel	1.4122	-10	80	13527712
DN65	PN16	PN10/16	46	NBR	Stainless steel	1.4122	-10	80	13527714
DN80	PN16	PN10/16	46	NBR	Stainless steel	1.4122	-10	80	13527716
DN100	PN16	PN10	52	NBR	Stainless steel	1.4122	-10	80	13527718
DN125	PN16	PN10	56	NBR	Stainless steel	1.4122	-10	80	13527720
DN200	PN10	PN10	60	NBR	Stainless steel	1.4122	-10	80	13527724

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.