

EWELLIX Linear actuator DC version series Matrix 1



Characteristics

Series: Matrix 1

Temperature range: 0 / 40 °C

Manufacturer ID	Type of drive	Stroke mm	Speed mm/s	Nominal voltage V	Nominal current A	Protection class	Article
MAX10-A100295AC510F-000	Trapezoidal screw	100	7	24	5	IP66S	13216581
MAX10-A150345AC510F-000	Trapezoidal screw	150	7	24	5	IP66S	13216574
MAX10-A200395AC510F-000	Trapezoidal screw	200	7	24	5	IP66S	13216608
MAX10-C200395AC51MF-000	Trapezoidal screw	200	18	24	5	IP66S	13216606
MAX10-A250445AC510F-000	Trapezoidal screw	250	7	24	5	IP66S	13216599
MAX10-A300495AC510F-000	Trapezoidal screw	300	7	24	5	IP66S	13216570
MAX10-A350545AC510F-000	Trapezoidal screw	350	7	24	5	IP66S	13216694
MAX10-A400660AC510F-000	Trapezoidal screw	400	7	24	5	IP66S	13216600
MAX10-C500760AC51MF-000	Trapezoidal screw	500	18	24	5	IP66S	13216585

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.