



Hose coupling AISI 316 with Tri-clamp (clamp liner) type SHTC DIN 11864-3 BKF, Form A; size according to DIN R2

Characteristics

Type of component: Hose tail coupling

Material: AISI 316

Connection type: Triclamp

Hose fitting type: Tri-Clamp DIN 11864-3 BKS

Connection termination: DIN 11864-3 BKS - DIN R2

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -10 / 140 °C

Application

- Recommended in: Food & Beverages

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
34,0/ 19,0x1,5 [16,0]	DN12	40	580	13034159
34,0/ 23,0x1,5 [20,0]	DN19	40	580	13034160
50,5/ 29,0x1,5 [26,0]	DN25	40	580	13034161
50,5/ 35,0x1,5 [32,0]	DN32	40	580	13034162
50,5/ 41,0x1,5 [38,0]	DN38	40	580	13034163
64,0/ 53,0x1,5 [50,0]	DN50	25	362	13034164
91,0/ 70,0x2,0 [66,0]	DN63	16	232	13034165
106,0/ 85,0x2,0 [81,0]	DN75	16	232	13034166
119,0/ 104,0x2,0 [100,0]	DN100	16	232	13034167

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.