



## Hose coupling AISI 316 with Tri-clamp (clamp nut) type SHTC DIN 11864-3 NKF, Form A; size according to ISO

### Characteristics

**Type of component:** Hose tail coupling

**Material:** AISI 316

**Connection type:** Triclamp

**Hose fitting type:** Tri-Clamp DIN 11864-3 NKS

**Connection termination:** DIN 11864-3 NKS - ISO

**Elbow angle [degr.]:** 0 °

**Hose tail execution:** Serrated, with safety collar

**Temperature range [°C]:** -10 / 140 °C

### Application

- Recommended in: Food & Beverages

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
34,0/ 21,3x1,6 [18,1]	DN12	40	580	13034169
34,0/ 17,2x1,6 [14,0]	DN12	40	580	13034168
50,5/ 26,6x1,6 [23,7]	DN19	40	580	13034170
50,5/ 33,7x2,0 [29,7]	DN25	40	580	13034171
64,0/ 42,4x2,0 [38,4]	DN32	25	362	13034172
64,0/ 48,3x2,0 [44,3]	DN38	25	362	13034173
77,0/ 60,3x2,0 [56,3]	DN50	16	232	13034174
106,0/76,1x2,0 [72,1]	DN63	16	232	13034175
119,0/ 88,9x2,0 [84,3]	DN75	16	232	13034176
130,0/ 114,3x2,0 [109,7]	DN100	16	232	13034177

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.