



ECON® Switchbox Type: 79652 Aluminium

Characteristics

- Type:** 79652
Execution: Switchbox
Explosion-proof: No
With console: Yes
Console height: 30 mm
Standard actuator connection: NAMUR (VDI/VDE 3845)
Distance of mounting holes: 80x30 mm
Length drive shaft: 17 mm
With mechanical setting indicator: Yes
Surface protection: Powder coating
Material shaft: Stainless steel
O-ring material: NBR
Material konsole: Stainless steel 304
Ambient temperature: -20 / 80 °C

Application

- Feedback on the opening and closing position for manually, pneumatically and hydraulically operated ball valves, butterfly valves and plug valves.
- Industrial and maritime applications.

Technical Information

- For mounting on actuators with VDI/VDE 3845 connection.
- IP67 aluminium casing.
- Includes stainless steel mounting bracket [80mm x 30mm x 30mm (LxWxH)] as standard, other dimensions available on request.
- With two pieces (1x open and 1x closed) mechanical V3 switches.
- With four pieces (2x open and 2x closed) mechanical V3 switches.
- With a 4-20mA position feedback (CPT-Current Position Transmitter) including two mechanical V3 switches
- Suitable for ambient temperatures from -20°C to +80°C.

Options

- Optical position indicator for three-way valves with L- or T-bore.
- Assembly set for the use of manually operated (handle or worm gear) ball valves, butterfly valves or plug valves.
- Available with inductive V3 switches
- Available with 1 kΩ or 10 kΩ potentiometer.

Switch model	Type of switch	Number of switches	Supply voltage	Electrical connection	Level of protection (IP value)	Solenoid connection	Material housing	Article
Mechanical V3	Mechanical	2	250 V AC 16A	2x M20x1,5	IP67	Yes	Aluminium	13452281
Mechanical V3	Mechanical	4	250 V AC 16A	2x M20x1,5	IP67	Yes	Aluminium	13491880

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.