



ECON® Ball valve Type: 7752ES Stainless steel Pneumatic operated Single acting, spring closing Internal thread (BSPP) 1000 PSI WOG



Mounted pneumatically operated 2-way ball valve consisting of: Two-piece Econ® ball valve (type: 7752ISO) and single-acting pneumatic Econ® actuator (type: 7901).



The pneumatically operated 2-way ball valve is configured according to the following basic principles: Pneumatic pilot pressure at 6 bar, medium is water, medium temperature is max. 100°C, ball valve is actuated at least a few times daily, actuator structure according to Eriks standard.

Characteristics

Type: 7752ES
Norm: EN (DIN)
Construction type: 2-way
Housing construction: 2-part
Housing material: Stainless steel
Material quality: 1.4408
Connection: Internal thread (BSPP)
Actuator: Pneumatic operated
Operating principle: Single acting, spring closing
Primary spindle seal material: PTFE
Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: PTFE
Body seal: PTFE
Actuator material: Aluminium

Application

- Compressed air, central heating systems, water, fuel and slightly corrosive systems up to a maximum of 68 bar.

Technical Information

- Connection according to ISO 228-1 BSPP.
- Pressure class 1000 PSI WOG
- In sizes 0.25-3 inches
- Actuator with multifunctional position indicator, suitable for mechanical limit switches or double proximity sensors.
- Air supply and upper flanged connection of drive in accordance with NAMUR VDI/VDE 3845.

Construction

- Two-piece housing construction.
- Design in accordance with EN 12516-2.
- Full bore.
- Equipped with anti-static design between ball, spindle and housing.

Approval


- TA Luft certified in accordance with VDI 2440, section 3.3.1.3.
- Declaration of conformity according to EC 1935/2004.

Options

- With double acting pneumatic drive, type 7752ED
- End of service life signalling through switch box or double sensor, type 79650 to 79659
- Positioner, type 3303
- Namur control valve, type 33580
- Stainless-steel extended spindle for insulation (type 8007)
- Connection in NPT according to ASME B1.20.1.

Ball Valves | Automated ball valves with threaded connection

Size table:



DN	d mm	L mm	H mm	B mm	Weight kg
1/4" [8]	10.6	64	138	81.5	1.9
3/8" [10]	12.7	64	138	81.5	1.9
1/2" [15]	15	64	138	81.5	2
3/4" [20]	20	70	145	81.5	2.1
1" [25]	25	85	173	97.5	3.3
1.1/4" [32]	32	94	200	108.5	5.1
1.1/2" [40]	38	105	219	128	7
2" [50]	50	125	243	149.5	10.9
2.1/2" [65]	63.5	155	265	149.5	13.8
3" [80]	76	173	308	198.5	24.6

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Bore	Material ball	Seat material	Spindle material	Article
1/4" [8]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR20	ECON	Full bore	1.4408	PTFE	1.4401	13509880
3/8" [10]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR20	ECON	Full bore	1.4408	PTFE	1.4401	13509881
1/2" [15]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR20	ECON	Full bore	1.4408	PTFE	1.4401	13509882
3/4" [20]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR20	ECON	Full bore	1.4408	PTFE	1.4401	13509883
1" [25]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR40	ECON	Full bore	1.4408	PTFE	1.4401	13509884
1.1/4" [32]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR80	ECON	Full bore	1.4408	PTFE	1.4401	13509885
1.1/2" [40]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR130	ECON	Full bore	1.4408	PTFE	1.4401	13509886
2" [50]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR200	ECON	Full bore	1.4408	PTFE	1.4401	13509887
2.1/2" [65]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR200	ECON	Full bore	1.4408	PTFE	1.4401	13509888
3" [80]	ISO 228-1	1000 PSI WOG	Manufacturer standard	SR500	ECON	Full bore	1.4408	PTFE	1.4401	13509889

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.