

FENNER Wedge belt Quattro PLUS twin wrapped narrow section QSPA



Fenner

®

Quattro PLUS TW

Heavy duty, twin wrapped wedge belt

The Fenner® Quattro PLUS TW is a wrapped belt that has been specifically designed with a 2 ply outer jacket to reduce belt elongation and improve stability. Suitable for a wide range of industries and uses, this maintenance free belt transmits 30% more power than traditional wrapped wedge belts.

Characteristics

Series: Quattro PLUS TW

Type: QSPA

Height: 10 mm

Width (top): 13 mm

Material: CR (polychloroprene)

Tensile Cord: Polyester (PES)

Sheathed: Yes

Shape-toothed model: No

Double V-profile model: No

With perforation: 0

With top layer: No

Temperature resistance: -30 / 80 °C

Execution

- Suitable for counterbending / back-tensioners ► Suitable for clutches

Approval

- Fully approved by all international standards
 - BS 3790 (British Standard) ► ISO 4184 (International Standards Organisation) ► DIN 7753 (German Institute for Standardization) ► Static conductive in accordance with ISO 1813 ► Conforms to API (American Petroleum Institute) specifications

Technical Information

- Extended temperature range -30° to +80°C. ► PB® (Precision Built) technology, eliminating the need for matching ► Conditionally oil resistant

Construction

- State-of-the-art wrapped chloroprene rubber construction ► Higher modulus polyester cord reduces belt elongation ► 2-ply outer jacket improves belt length stability and improves abrasion resistance

Reference length [ISO] mm	Article
1207	SPA1207QPTW-FEN
1232	SPA1232QPTW-FEN
1250	SPA1250QPTW-FEN
1257	SPA1257QPTW-FEN
1272	SPA1272QPTW-FEN
1282	SPA1282QPTW-FEN
1307	SPA1307QPTW-FEN
1320	SPA1320QPTW-FEN
1332	SPA1332QPTW-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Reference length (ISO) mm	Article
1357	SPA1357QPTW-FEN
1382	SPA1382QPTW-FEN
1400	SPA1400QPTW-FEN
1432	SPA1432QPTW-FEN
1457	SPA1457QPTW-FEN
1482	SPA1482QPTW-FEN
1500	SPA1500QPTW-FEN
1532	SPA1532QPTW-FEN
1557	SPA1557QPTW-FEN
1582	SPA1582QPTW-FEN
1600	SPA1600QPTW-FEN
1632	SPA1632QPTW-FEN
1657	SPA1657QPTW-FEN
1682	SPA1682QPTW-FEN
1700	SPA1700QPTW-FEN
1732	SPA1732QPTW-FEN
1757	SPA1757QPTW-FEN
1782	SPA1782QPTW-FEN
1800	SPA1800QPTW-FEN
1832	SPA1832QPTW-FEN
1857	SPA1857QPTW-FEN
1882	SPA1882QPTW-FEN
1900	SPA1900QPTW-FEN
1932	SPA1932QPTW-FEN
1957	SPA1957QPTW-FEN
1982	SPA1982QPTW-FEN
2000	SPA2000QPTW-FEN
2032	SPA2032QPTW-FEN
2057	SPA2057QPTW-FEN
2120	SPA2120QPTW-FEN
2132	SPA2132QPTW-FEN
2182	SPA2182QPTW-FEN
2207	SPA2207QPTW-FEN
2232	SPA2232QPTW-FEN
2240	SPA2240QPTW-FEN
2282	SPA2282QPTW-FEN
2300	SPA2300QPTW-FEN
2332	SPA2332QPTW-FEN
2360	SPA2360QPTW-FEN
2432	SPA2432QPTW-FEN
2482	SPA2482QPTW-FEN
2500	SPA2500QPTW-FEN
2532	SPA2532QPTW-FEN
2582	SPA2582QPTW-FEN
2607	SPA2607QPTW-FEN
2650	SPA2650QPTW-FEN
2682	SPA2682QPTW-FEN
2732	SPA2732QPTW-FEN
2782	SPA2782QPTW-FEN
2800	SPA2800QPTW-FEN
2832	SPA2832QPTW-FEN
2847	SPA2847QPTW-FEN
2882	SPA2882QPTW-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Reference length (ISO) mm	Article
2932	SPA2932QPTW-FEN
2982	SPA2982QPTW-FEN
3000	SPA3000QPTW-FEN
3032	SPA3032QPTW-FEN
3082	SPA3082QPTW-FEN
3150	SPA3150QPTW-FEN
3182	SPA3182QPTW-FEN
3282	SPA3282QPTW-FEN
3350	SPA3350QPTW-FEN
3382	SPA3382QPTW-FEN
3550	SPA3550QPTW-FEN
3650	SPA3650QPTW-FEN
3750	SPA3750QPTW-FEN
3870	SPA3870QPTW-FEN
4000	SPA4000QPTW-FEN
4250	SPA4250QPTW-FEN
4500	SPA4500QPTW-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.