ECON® Ball valve Type: 1615 Brass KIWA Internal thread (BSPP)/External thread (BSPT) PN10





Type: 1615 Norm: EN (DIN)

Construction type: 2-way Housing construction: 2-part Housing material: Brass Material quality: CW617N

Connection: Internal thread (BSPP)
Connection 2: External thread (BSPT)
Secondary spindle seal material: NBR

Actuator material: 1.4301

KIWA: Yes

Application

• Drinking water systems up to 25°C.

Technical Information

- Connections with male and female threads in accordance with EN 10226-1 (ISO 7/1 Rp).
- Ball valve with floating ball.
- Version with lever.
- Available in sizes ranging from 3/8" to 2".
- Pressure class PN10.

Construction


- Two-piece housing construction.
- Full bore.
- Face-to-face dimension according to manufacturer's standard.

Approval

 With KIWA, DVGW and ACS approvals for drinking water systems.

Options

• Available with extended spindle.



Size table:

DN	d	L	Н	М	Weight
	mm	mm	mm	mm	kg
3/8" (10)	10	54	41	80	0.19
1/2" (15)	15	70	54	90	0.21
3/4" [20]	20	80	58	90	0.35
1" (25)	25	92	66	125	0.54
1.1/4" [32]	32	102	71	125	0.84
1.1/2" [40]	40	117	80	140	1
2" (50)	50	137	88	140	1.7

Pressure and temperature range							
Size	Pressure class	-10	70	[°C]			
3/8" - 2"	PN10	10	10	[bar]			

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR9274769061242399_EN_30.06.2024

Ball Valves | Ball valves with threaded connection

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
3/8" (10)	ISO 7/1 Rp/R	PN10	Manufacturer standard	Handle	Full bore	CW617N chromed	PTFE	Brass	NBR	12725775
1/2" (15)	ISO 7/1 Rp/R	PN10	Manufacturer standard	Handle	Full bore	CW617N chromed	PTFE	Brass	NBR	12725772
3/4" [20]	ISO 7/1 Rp/R	PN10	Manufacturer standard	Handle	Full bore	CW617N chromed	PTFE	Brass	NBR	12725774
1" (25)	ISO 7/1 Rp/R	PN10	Manufacturer standard	Handle	Full bore	CW617N chromed	PTFE	Brass	NBR	12725770
1.1/4" (32)	ISO 7/1 Rp/R	PN10	Manufacturer standard	Handle	Full bore	CW617N chromed	PTFE	Brass	NBR	12725771
1.1/2" [40]	ISO 7/1 Rp/R	PN10	Manufacturer standard	Handle	Full bore	CW617N chromed	PTFE	Brass	NBR	12452285
2" (50)	ISO 7/1 Rp/R	PN10	Manufacturer standard	Handle	Full bore	CW617N chromed	PTFE	Brass	NBR	12725773

e or e advice. Page 2/4769061242399_EN_30.06.2024 Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.