



SMC Speed Controller with Indicator, Elbow type series AS-FS

- 4 different indicator window orientations.
- Wide range of tubing, port sizes and thread types.
- Easy identification of product with colour differentiation: meter-in/meter-out and inch/metric sizes.
- Many made to order options available.

Characteristics

Series: AS-FS

Execution: Flow/check valve

Mounting: Threaded

Material housing: PBT/Nickel-plated brass

Seal material: NBR

Operating pressure: 1 / 10 bar

Temperature range: -5 / 60 °C

Fluid: Compressed air in accordance with ISO8573-1:2010

Port thread type	Pneumatic connection 1	Article
		13468650
		13468653
		13468645
		13468638
BSPT (R)	1/4	13468647
BSPT (R)	1/4	13616724
BSPT (R)	1/8	13468641
BSPT (R)	1/8	13468635
BSPT (R)	1/8	13964342
BSPT (R)	3/8	13468652
External thread (Metric)	M 5	14011403

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.