



CUS SA Telescopic cylinders with eye heavy P-Series

Characteristics

Type: Telescopic cylinder with eye P-series

Type [DA/SA]: Single acting

Max. operating pressure: 180 bar

Front fixation: Eye

Rear fixation: Mounting lugs

Max. load at max. working pressure kg	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
12000	7	61/76/91/107/127/146/166	1500	368	BSP female 3/4" BSP	12558969
12000	7	61/76/91/107/127/146/166	1750	403	BSP female 3/4" BSP	12558970
12000	7	61/76/91/107/127/146/166	2100	453	BSP female 3/4" BSP	12558971
12000	7	61/76/91/107/127/146/166	2600	523	BSP female 3/4" BSP	12558972
12000	7	61/76/91/107/127/146/166	3000	583	BSP female 3/4" BSP	12558973
12000	7	61/76/91/107/127/146/166	3500	653	BSP female 3/4" BSP	12558974
18000	6	72/91/107/127/146/166	1500	409	BSP female 3/4" BSP	12558976
18000	6	72/91/107/127/146/166	1800	459	BSP female 3/4" BSP	12558977
18000	6	72/91/107/127/146/166	2220	529	BSP female 3/4" BSP	12558978
18000	6	72/91/107/127/146/166	2600	589	BSP female 3/4" BSP	12558979
18000	6	72/91/107/127/146/166	3000	709	BSP female 3/4" BSP	12558981
18000	6	72/91/107/127/146/166	3300	709	BSP female 3/4" BSP	12558982
18000	6	72/91/107/127/146/166	3600	759	BSP female 3/4" BSP	12558983
20000	5	91/107/127/146/166	1250	407	BSP female 3/4" BSP	12558985
20000	5	91/107/127/146/166	1500	457	BSP female 3/4" BSP	12558986
20000	5	91/107/127/146/166	1850	527	BSP female 3/4" BSP	12558988
20000	5	91/107/127/146/166	2150	587	BSP female 3/4" BSP	12558989
20000	5	91/107/127/146/166	2500	657	BSP female 3/4" BSP	12558990
20000	5	91/107/127/146/166	2750	707	BSP female 3/4" BSP	12558991
20000	5	91/107/127/146/166	3000	757	BSP female 3/4" BSP	12558992
22000	4	107/127/144/166	2200	713	BSP female 3/4" BSP	12559000
22000	4	107/127/146/166	1000	413	BSP female 3/4" BSP	12558994
22000	4	107/127/146/166	1200	463	BSP female 3/4" BSP	12558995
22000	4	107/127/146/166	1500	533	BSP female 3/4" BSP	12558996
22000	4	107/127/146/166	1720	593	BSP female 3/4" BSP	12558998
22000	4	107/127/146/166	2000	663	BSP female 3/4" BSP	12558999
22000	4	107/127/146/166	2400	763	BSP female 3/4" BSP	12559001

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.