



PFERD Hard cutting disc, SG steel, hardness: S

Wheel thicknesses 1.9/1.6/1.0 mm for fast, easy cutting with minimized burr formation Wheel thickness 2.4 mm for multipurpose cutting work

Wheel thicknesses 3.2/3.0/2.9 mm for maximum tool life with high lateral stability Suitable for use on angle grinders of all output categories The use of large clamping flanges [SFS 76, page 48] increases the lateral stability and ensures precise wheel guidance, in particular for thin cut-off wheels of the flat type with dia. 178 and 230 mm - Abrasive: Aluminium oxide A - Hard, high-performance tool of hardness S with high cutting performance and very long tool life.

- PFERDVIDEO You will receive more information here or at www.pferd.com - Steel - Cutting of sheet metal, profiles and solid material

Diameter disc mm	Thickness mm	Granulation	Article
100	2.4	46	23875419
125	2.4	30	23148742
125	2.4	30	23875340
125	3.2	30	23875338
150	3	24	23875341
150	3	24	23875342
230	2.9	24	23875369
230	3.2	24	23875350
			23148740

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.