

PFERD Medium-hard cutting disc, PSF stone/aluminium/nonferrous metals, hardness: P

Wheel thicknesses 1.6/1.0 mm for fast, easy cutting with minimized burr formation Wheel thickness 2.4 mm for multipurpose cutting work

Wheel thicknesses 3.2/3.0 mm for maximum tool life with high lateral stability Suitable for use on angle grinders of all output categories

- Abrasive: Silicon carbide C
- Medium-hard, multipurpose tool of hardness P (C) with high cutting performance and long tool life.
- Natural stone, synthetic stone, fire-resistant stone, aluminium, non-ferrous metals Cutting of solid material

Diameter disc	Thickness	Granulation	Article
mm	mm		
115	1	60	23875476
115	2.4	30	23875484
125	2.4	30	23875478
150	3	24	23875480
178	3.2	24	23875482
230	3.2	24	23875483
230	3.2	24	23875481

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: gereedschappen@eriks.nl

PR_EC000173_0130_EN_30.06.2024