


## DIN7983H Raised countersunk tapping screw with Phillips cross recess Steel zinc plated



### Characteristics

**Series:** DIN 7983H

**Head form:** Countersunk head (oval)

**Screwing system:** Phillips

**Surface protection:** Galvanic/electrolytic zinc plated

**With point:** Yes

**Self drilling:** No

**DIN standard:** 7983

**Type:** Sheet metal screw

Material	Thread diameter		Length		Article
	mm		mm		
Carbon steel	2.9		9		23693587
Carbon steel	2.9		13		11791312
Carbon steel	2.9		19		23693588
Carbon steel	3.5		9		23693590
Carbon steel	3.5		13		23693591
Carbon steel	3.5		16		11791315
Carbon steel	3.5		25		23693593
Carbon steel	3.5		32		23693594
Carbon steel	3.5		38		23693595
Carbon steel	3.9		9		23693596
Carbon steel	3.9		13		23693597
Carbon steel	3.9		19		23693598
Carbon steel	3.9		38		11791318
Carbon steel	4.2		19		11791320
Carbon steel	4.2		22		23693605
Carbon steel	4.2		32		11791322
Carbon steel	4.2		45		23693606
Carbon steel	4.8		13		23693607
Carbon steel	4.8		16		11791326
Carbon steel	4.8		19		23693608
Carbon steel	4.8		22		23693609
Carbon steel	4.8		25		11791327
Carbon steel	4.8		50		23693611
Carbon steel	5.5		16		23693613
Carbon steel	5.5		19		11791333
Carbon steel	5.5		25		11791334
Carbon steel	5.5		32		23693615
Carbon steel	5.5		38		11791335
Carbon steel	6.3		25		23693621
Carbon steel	6.3		50		23693625

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.