


## DIN7982Z Countersunk tapping screw with Pozidriv cross recess Stainless steel A2



### Characteristics

**Series:** DIN 7982Z

**Head form:** Countersunk head

**Screwing system:** Pozidriv

**Material quality:** Stainless steel A2

**Surface protection:** Untreated

**With point:** Yes

**Self drilling:** No

**DIN standard:** 7982

**Type:** Sheet metal screw

Material	Thread diameter		Article
	mm	mm	
Stainless steel	2.9	9.5	23730966
Stainless steel	2.9	16	23730963
Stainless steel	2.9	25	23267359
Stainless steel	3.5	9.5	23267360
Stainless steel	3.5	9.5	23730973
Stainless steel	3.9	16	23267368
Stainless steel	4.2	19	23267374
Stainless steel	4.2	25	23730982
Stainless steel	4.2	32	23730983
Stainless steel	4.2	45	23730985
Stainless steel	4.2	50	23267379
Stainless steel	4.8	16	23267380
Stainless steel	4.8	19	23267381
Stainless steel	4.8	25	23267382
Stainless steel	4.8	25	23730989
Stainless steel	4.8	50	23267386
Stainless steel	6.3	50	23731004

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.