

GUHRING Carbide-tipped twist drill type 703

Characteristics

Cutting direction: Right

DIN standard: 8037

Type: Twist drill

Point angle: 118 °



Diameter mm	Cutting length mm	Total length mm	Holding system	Material	Article
1.7	18	45	Cylindrical	Hard metal	11969531
3	20	50	Cylindrical	Hard metal	11969538
3.5	25	56	Cylindrical	Hard metal	11969544
4	25	56	Cylindrical	Hard metal	11969550
4.2	28	63	Cylindrical	Hard metal	11969552
4.5	28	63	Cylindrical	Hard metal	11969555
5	28	63	Cylindrical	Hard metal	11969559
5.1	32	71	Cylindrical	Hard metal	11969560
5.2	32	71	Cylindrical	Hard metal	11969561
5.5	32	71	Cylindrical	Hard metal	11969564
5.8	32	71	Cylindrical	Hard metal	11969567
6	32	71	Cylindrical	Hard metal	11969569
6.5	32	71	Cylindrical	Hard metal	11969575
6.8	40	80	Cylindrical	Hard metal	11969578
7	40	80	Cylindrical	Hard metal	11969580
7.5	40	80	Cylindrical	Hard metal	11969585
8	40	80	Cylindrical	Hard metal	11969591
8.5	50	90	Cylindrical	Hard metal	11969596
9	50	90	Cylindrical	Hard metal	11969601
9.5	50	90	Cylindrical	Hard metal	11969605
10	56	100	Cylindrical	Hard metal	11969609
10.2	56	100	Cylindrical	Hard metal	11969610
10.5	56	100	Cylindrical	Hard metal	11969612
11	56	100	Cylindrical	Hard metal	11969615
11.5	63	112	Cylindrical	Hard metal	11969617
12	63	112	Cylindrical	Hard metal	11969621
13	63	112	Cylindrical	Hard metal	11969624

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.