

GUHRING Spiral drill bit type 1262

Design: Right cutting, with precise point geometry and excellent thermal resistance. Without point thinning. Angle of rake larger than normal, core thickness thinner than normal and normal core gradient.



Application: Particularly suitable for rust/acid/heat-resistant and austenitic steels (INOX).

Characteristics

Cutting direction: Right

DIN standard: 345

Type: Twist drill

Point angle: 130 °

Diameter mm	Cutting length mm	Total length mm	Holding system	Material	Article
15.5	120	218	Morseconus 2	HSS-co	W90A-10821550
16	120	218	Morseconus 2	HSS-co	W90A-10821600
16.5	125	223	Morseconus 2	HSS-co	W90A-10821650
17	125	223	Morseconus 2	HSS-co	W90A-10821700
18	130	228	Morseconus 2	HSS-co	W90A-10821800
19.5	140	238	Morseconus 2	HSS-co	W90A-10821950
30	175	296	Morseconus 3	HSS-co	W90A-10823000

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.