## **FORMAT Spiral drill bit type 1089**













Design: HSS, DIN 341, type N.

Profile grinding, steam tempered surface, right cutting, with precise point geometry. Good centring characteristics due to point thinning according to DIN 1412, form A. Angle of rake, core thickness and core gradient normal.

Application: Suitable for drilling through boring bushes (important for sloped and uneven surfaces) as well as drilling deep holes up to 10 x D. Particularly suitable for alloyed and non-alloyed steels, steel casting, grey cast iron, malleable cast iron, nodular iron, sintered iron, nickel silver and graphite.

## **Characteristics**

**Cutting direction: Right** DIN standard: 341 Type: Twist drill Point angle: 118°

Diameter	Cutting length	Total length	Model	Holding system	Material	Article
mm	mm	mm				
10	116	197	Profile-cut	Morseconus 1	HSS	W90A-10891000
10.5	116	197	Profile-cut	Morseconus 1	HSS	W90A-10891050
11	125	206	Profile-cut	Morseconus 1	HSS	W90A-10891100
11.5	125	206	Profile-cut	Morseconus 1	HSS	W90A-10891150
12	134	215	Profile-cut	Morseconus 1	HSS	W90A-10891200
12.5	134	215	Profile-cut	Morseconus 1	HSS	W90A-10891250
13	134	215	Profile-cut	Morseconus 1	HSS	W90A-10891300
14	142	223	Profile-cut	Morseconus 1	HSS	W90A-10891400
15	147	245	Profile-cut	Morseconus 2	HSS	W90A-10891500
15.5	153	251	Profile-cut	Morseconus 2	HSS	W90A-10891550
16	153	251	Profile-cut	Morseconus 2	HSS	W90A-10891600
17	159	257	Profile-cut	Morseconus 2	HSS	W90A-10891700
18	165	263	Profile-cut	Morseconus 2	HSS	W90A-10891800
19	171	269	Profile-cut	Morseconus 2	HSS	W90A-10891900
20	177	275	Profile-cut	Morseconus 2	HSS	W90A-10892000
21	184	282	Profile-cut	Morseconus 2	HSS	W90A-10892100
21.5	191	289	Profile-cut	Morseconus 2	HSS	W90A-10892150
22	191	289	Profile-cut	Morseconus 2	HSS	W90A-10892200
23	198	296	Profile-cut	Morseconus 2	HSS	W90A-10892300
24	206	327	Profile-cut	Morseconus 3	HSS	W90A-10892400
25	206	327	Profile-cut	Morseconus 3	HSS	W90A-10892500
26	214	335	Profile-cut	Morseconus 3	HSS	W90A-10892600
27	222	343	Profile-cut	Morseconus 3	HSS	W90A-10892700
28	222	343	Profile-cut	Morseconus 3	HSS	W90A-10892800
29	230	351	Profile-cut	Morseconus 3	HSS	W90A-10892900
30	230	351	Profile-cut	Morseconus 3	HSS	W90A-10893000
31	239	360	Profile-cut	Morseconus 3	HSS	W90A-10893100
32	248	397	Profile-cut	Morseconus 4	HSS	W90A-10893200
33	248	397	Profile-cut	Morseconus 4	HSS	W90A-10893300
34	257	406	Profile-cut	Morseconus 4	HSS	W90A-10893400
35	257	406	Profile-cut	Morseconus 4	HSS	W90A-10893500
36	267	416	Profile-cut	Morseconus 4	HSS	W90A-10893600

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/2

PR\_EC000945\_0561\_EN\_29.06.2024

Diameter	Cutting length	Total length	Model	Holding system	Material	Article
mm	mm	mm				
37	267	416	Profile-cut	Morseconus 4	HSS	W90A-10893700
38	277	426	Profile-cut	Morseconus 4	HSS	W90A-10893800
39	277	426	Profile-cut	Morseconus 4	HSS	W90A-10893900
40	277	426	Profile-cut	Morseconus 4	HSS	W90A-10894000
45	298	447	Profile-cut	Morseconus 4	HSS	W90A-10894500
50	321	470	Profile-cut	Morseconus 4	HSS	W90A-10895000
	142	223	Profile-cut	Morseconus 1	HSS	W90A-10891350
	147	245	Profile-cut	Morseconus 2	HSS	W90A-10891450
	159	257	Profile-cut	Morseconus 2	HSS	W90A-10891650
	165	263	Profile-cut	Morseconus 2	HSS	W90A-10891750
	171	269	Profile-cut	Morseconus 2	HSS	W90A-10891850
	177	275	Profile-cut	Morseconus 2	HSS	W90A-10891950
	184	282	Profile-cut	Morseconus 2	HSS	W90A-10892050
	198	296	Profile-cut	Morseconus 2	HSS	W90A-10892250

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

**ERIKS**