

FORMAT HSS sheet cutter type 1300



Fabrieks-
norm

Design: According to factory standard, CBN deep sharpened, straight fluted.
Chuck slippage is avoided by the 3-surface shank. With cross point and laser print of hole Ø and speed. The hole Ø can still be read with the tool rotating.

Application: For burr-free drilling and reaming of sheets, pipes and profiles. Works without burrs and chatter marks and can be used in hand drills and box column drills. No punch marking required.

For steel plate 0.1?2.0 mm

Nirosta sheet (V2A) 0.1?1.0 mm

Plastics up to 10.0 mm

Non-ferrous metals 0.1?5.0 mm

Note: To increase the service life, we recommend the use of drilling paste [order no. 1312 0005].

Characteristics

Cutting direction: Right

Type: Stepped drill

Total length mm	Material	Article
58	HSS-co	23410294
66	HSS-co	23410295
72	HSS-co	23410296
86	HSS-co	23410297
87	HSS-co	23410298
91	HSS-co	23410299
104	HSS-co	23410300

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.