


DORMER HSCo short production drill bit with cylindrical shank DIN 338 uncoated 6xD type A900



HSS-E jobber length productivity drill PFX with cylindrical shank DIN 338 130° 6xD bright finish for steel

Characteristics

DIN standard: 338

Type: Twist drill

Point angle: 130 °

Diameter mm	Diameter in	Cutting length mm	Total length mm	Holding system	Material	Article
2.2		27	53	Cylindrical	HSS-co	11919647
2.7		33	61	Cylindrical	HSS-co	11919652
3.3		36	65	Cylindrical	HSS-co	11919664
4.2		43	75	Cylindrical	HSS-co	11919677
4.5		47	80	Cylindrical	HSS-co	11919680
5.1		52	86	Cylindrical	HSS-co	11919686
6.8		69	109	Cylindrical	HSS-co	11919706
8		75	117	Cylindrical	HSS-co	11919721
8.5		75	117	Cylindrical	HSS-co	11919726
10		87	133	Cylindrical	HSS-co	11919612
11		94	142	Cylindrical	HSS-co	11919618
12.7	1/2	114	152	Cylindrical	HSS-co	11919609

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.