


## SKF Strong back puller series TMBS..E



- The TMBS E strong back pullers facilitate dismounting of bearings in applications where the use of traditional jaw pullers is restricted due to lack of space or where the application demands a long reach. Special separator design allows the puller to be easily inserted between the bearing and the shoulder on the shaft
- The spring-loaded centre point of the hydraulic spindle allows easy puller centring
- The firm grip behind the bearing's inner ring reduces the force required to dismount the bearing
- The hydraulic spindle is equipped with a safety valve, which minimises the risk of puller overload
- A hydraulic spindle stroke of 80 mm helps facilitate dismounting in one operation
- TMBS 50E is equipped with a mechanical spindle for force generation
- TMBS 100E and the TMBS 150E are equipped with a hydraulic spindle, which allows for easy application of force up to 100 kN
- Supplied with hydraulic spindle extension pieces to allow quick adaptation to pulling length
- TMBS 100E and TMBS 150E are supplied with extension rods to allow quick adaptation to pulling lengths upto 816 mm

### Characteristics

**Series:** TMBS

Clamping spread mm	Article
7-50	23770439
20-100	23770426
35-150	23770433

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.