


FORMAT Hand taper tap form A, HSS metric type 1600



Design: HSS, DIN 352, tolerance range ISO 2/6H, type N, bright surface.

Application: For regular metric threads according to ISO DIN 13. Particularly suitable for high strength materials up to 1200 N/mm² in strength and rust-free and acid-resistant steels.

Characteristics

Kind of thread: Metric

DIN standard: 352

Kind of thread	Thread size metric (M...)	Pitch inner thread	DIN standard	Material	Total length	Article
		mm			mm	
Metric	1		352	HSS		23411563
Metric	1.2		352	HSS		23411564
Metric	1.4		352	HSS		23411565
Metric	1.6		352	HSS		23411566
Metric	1.7		352	HSS		23411567
Metric	2	0.4	352	HSS		23411568
Metric	2.2		352	HSS		23411569
Metric	2.3		352	HSS		23411570
Metric	2.5		352	HSS		23411571
Metric	2.6		352	HSS		23411572
Metric	3		352	HSS		23411573
Metric	3.5		352	HSS		23411574
Metric	4		352	HSS		23411575
Metric	4.5		352	HSS		23411576
Metric	5		352	HSS		23411577
Metric	6		352	HSS		23411578
Metric	7		352	HSS		23411579
Metric	8		352	HSS		23411580
Metric	9	1.25	352	HSS	63	23411581
Metric	9		352	HSS		23411583
Metric	10		352	HSS		23411582
Metric	12		352	HSS		23411584
Metric	14		352	HSS		23411585
Metric	16		352	HSS		23411586
Metric	18		352	HSS		23411587
Metric	20		352	HSS		23411588
Metric	22		352	HSS		23411589
Metric	24		352	HSS		23411590
Metric	27		352	HSS		23411591
Metric	30		352	HSS		23411592

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.