


## FORMAT Hand taper tap form A, HSS metric type 1600



Design: HSS, DIN 352, tolerance range ISO 2/6H, type N, bright surface.

Application: For regular metric threads according to ISO DIN 13. Particularly suitable for high strength materials up to 1200 N/mm<sup>2</sup> in strength and rust-free and acid-resistant steels.

### Characteristics

**Kind of thread:** Metric

**DIN standard:** 352

Kind of thread	Thread size metric (M...)	Pitch inner thread	DIN standard	Material	Total length	Article
		mm			mm	
Metric	1		352	HSS		W90A-16000010
Metric	1.2		352	HSS		W90A-16000012
Metric	1.4		352	HSS		W90A-16000014
Metric	1.6		352	HSS		W90A-16000016
Metric	1.7		352	HSS		W90A-16000017
Metric	2	0.4	352	HSS		W90A-16000020
Metric	2.2		352	HSS		W90A-16000022
Metric	2.3		352	HSS		W90A-16000023
Metric	2.5		352	HSS		W90A-16000025
Metric	2.6		352	HSS		W90A-16000026
Metric	3		352	HSS		W90A-16000030
Metric	3.5		352	HSS		W90A-16000035
Metric	4		352	HSS		W90A-16000040
Metric	4.5		352	HSS		W90A-16000045
Metric	5		352	HSS		W90A-16000050
Metric	6		352	HSS		W90A-16000060
Metric	7		352	HSS		W90A-16000070
Metric	8		352	HSS		W90A-16000080
Metric	9	1.25	352	HSS	63	W90A-16000090
Metric	9		352	HSS		W90A-16000110
Metric	10		352	HSS		W90A-16000100
Metric	12		352	HSS		W90A-16000120
Metric	14		352	HSS		W90A-16000140
Metric	16		352	HSS		W90A-16000160
Metric	18		352	HSS		W90A-16000180
Metric	20		352	HSS		W90A-16000200
Metric	22		352	HSS		W90A-16000220
Metric	24		352	HSS		W90A-16000240
Metric	27		352	HSS		W90A-16000270
Metric	30		352	HSS		W90A-16000300

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.