


FORMAT Hand bottoming tap form C, HSS metric type 1603



Design: HSS, DIN 352, tolerance range ISO 2/6H, type N, bright surface.

Application: For regular metric threads according to ISO DIN 13. Particularly suitable for high strength materials up to 1200 N/mm² in strength and rust-free and acid-resistant steels.

Characteristics

Kind of thread: Metric

DIN standard: 352

Kind of thread	Thread size metric (M..)	DIN standard	Material	Article
Metric	1	352	HSS	23411623
Metric	1.2	352	HSS	23411624
Metric	1.4	352	HSS	23411625
Metric	1.6	352	HSS	23411626
Metric	1.7	352	HSS	23411627
Metric	2	352	HSS	23411628
Metric	2.2	352	HSS	23411629
Metric	2.3	352	HSS	23411630
Metric	2.5	352	HSS	23411631
Metric	2.6	352	HSS	23411632
Metric	3	352	HSS	23411633
Metric	3.5	352	HSS	23411634
Metric	4	352	HSS	23411635
Metric	4.5	352	HSS	23411636
Metric	5	352	HSS	23411637
Metric	6	352	HSS	23411638
Metric	7	352	HSS	23411639
Metric	8	352	HSS	23411640
Metric	9	352	HSS	23411641
Metric	10	352	HSS	23411642
Metric	11	352	HSS	23411643
Metric	12	352	HSS	23411644
Metric	14	352	HSS	23411645
Metric	16	352	HSS	23411646
Metric	18	352	HSS	23411647
Metric	20	352	HSS	23411648
Metric	22	352	HSS	23411649
Metric	24	352	HSS	23411650
Metric	27	352	HSS	23411651
Metric	30	352	HSS	23411652

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.