


## FORMAT Hand taper tap form A, HSS pipe thread (G) type 1638



Design: HSS, DIN 5157, type N, bright surface.

Application: For pipe threads according to DIN ISO 228/1 (DIN 259). Particularly suitable for high strength materials up to 1200 N/mm<sup>2</sup> in strength and rust-free and acid-resistant steels.

### Characteristics

**Kind of thread:** G (BSP)

**DIN standard:** 5157

Kind of thread	Thread size in	Pitch inner thread in	DIN standard	Material	Article
G (BSP)	1/8	28	5157	HSS	W90A-16380001
G (BSP)	1/4	19	5157	HSS	W90A-16380003
G (BSP)	3/8	19	5157	HSS	W90A-16380005
G (BSP)	1/2	14	5157	HSS	W90A-16380007
G (BSP)	5/8	14	5157	HSS	W90A-16380009
G (BSP)	3/4	14	5157	HSS	W90A-16380011
G (BSP)	7/8	14	5157	HSS	W90A-16380013
G (BSP)	1	11	5157	HSS	W90A-16380015
G (BSP)	3/2	11	5157	HSS	W90A-16380019
G (BSP)	2	11	5157	HSS	W90A-16380021
G (BSP)	5/4	11	5157	HSS	W90A-16380017

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.