


FORMAT Machine tap with reinforced shaft, HSS, metric type 1676



Design: HSS-E, tolerance range ISO 2/6H, type N, with spiral point form B [4-5 threads].

Application: For regular metric threads according to ISO DIN 13. Particularly suitable for general steels, construction steels, machining steels, case-hardening steels and tempered steels.

Characteristics

Kind of thread: Metric

Colour code: Yellow-ring

DIN standard: 376

Kind of thread	Thread size metric (M..)	Pitch inner thread mm	Colour code	DIN standard	Material	Total length mm	Article
Metric	1			371	HSS-co		W90A-16760010
Metric	1.2			371	HSS-co		W90A-16760012
Metric	1.4			371	HSS-co		W90A-16760014
Metric	1.6			371	HSS-co		W90A-16760016
Metric	1.8			371	HSS-co		W90A-16760018
Metric	2			371	HSS-co		W90A-16760020
Metric	2.5			371	HSS-co		W90A-16760025
Metric	3			371	HSS-co		W90A-16760030
Metric	3			376	HSS-co		W90A-16790030
Metric	4			371	HSS-co		W90A-16760040
Metric	5			371	HSS-co		W90A-16760050
Metric	6			371	HSS-co		W90A-16760060
Metric	8			371	HSS-co		W90A-16760080
Metric	10	1.5	Yellow-ring	371	HSS-co	100	W90A-16760100

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.