

FORMAT Short machine tap, HSS, metric type 1738



Design: HSS-E, DIN 352, tolerance range ISO 2/6H, type N, with point form C (2?3 threads) for blind holes. Bright surface

Application: For regular metric threads according to ISO DIN 13.

Note: These taps can be used as both blind hole machine taps and as manual taps (finish taps only).

Characteristics

Kind of thread: Metric

DIN standard: 352

Kind of thread	Thread size metric [M..]	Pitch inner thread mm	DIN standard	Material	Article
Metric	3		352	HSS-co	W90A-17380030
Metric	4		352	HSS-co	W90A-17380040
Metric	5		352	HSS-co	W90A-17380050
Metric	6		352	HSS-co	W90A-17380060
Metric	8		352	HSS-co	W90A-17380080
Metric	10		352	HSS-co	W90A-17380100
Metric	12		352	HSS-co	W90A-17380120
Metric	16		352	HSS-co	W90A-17380160
Metric	20	2.5	352	HSS-co	W90A-17380200

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.