FORMAT Short machine tap, HSS, metric type 1738















Design: HSS-E, DIN 352, tolerance range ISO 2/6H, type N, with point form C (2?3 threads) for blind holes. Bright surface

Application: For regular metric threads according to ISO DIN 13.

Note: These taps can be used as both blind hole machine taps and as manual taps (finish taps only).

Characteristics

Kind of thread: Metric DIN standard: 352

Thread size metric (M)	Pitch inner thread	DIN standard	Material	Article
	mm			
3		352	HSS-co	23412302
4		352	HSS-co	23412303
5		352	HSS-co	23412304
6		352	HSS-co	23103009
8		352	HSS-co	23412306
10		352	HSS-co	23412307
12		352	HSS-co	23412308
16		352	HSS-co	23412309
20	2.5	352	HSS-co	23412310
	3 4 5 6 8 10 12	mm 3 4 5 6 8 10 12 16	mm 3 352 4 352 5 352 6 352 8 352 10 352 12 352 16 352	mm 3 352 HSS-co 4 352 HSS-co 5 352 HSS-co 6 352 HSS-co 8 352 HSS-co 10 352 HSS-co 12 352 HSS-co 16 352 HSS-co

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR_EC002155_0953_EN_26.06.2024