

SPAX Chipboard screw full thread Flat countersunk head Pozidriv Hardenend Stainless steel A2



Characteristics

Material quality: Stainless steel A2

Surface protection: Untreated

Head form: Countersunk head

Type: Chipboard screw

Material	Screwing system	Diameter mm	Length mm	Article
Stainless steel	Pozidriv	3	12	11843166
Stainless steel	Pozidriv	3	16	11843167
Stainless steel	Pozidriv	3	25	11843169
Stainless steel	Pozidriv	3	30	11843170
Stainless steel	Pozidriv	3.5	16	11843173
Stainless steel	Pozidriv	3.5	25	11843175
Stainless steel	Pozidriv	3.5	30	11843176
Stainless steel	Pozidriv	3.5	35	11843177
Stainless steel	Pozidriv	3.5	40	11843178
Stainless steel	Pozidriv	4	20	11843179
Stainless steel	Pozidriv	4	25	11843180
Stainless steel	Pozidriv	4	40	11843183
Stainless steel	Pozidriv	4	45	11843184
Stainless steel	Pozidriv	4	60	11843186
Stainless steel	Pozidriv	4.5	25	11843187
Stainless steel	Pozidriv	4.5	30	11843188
Stainless steel	Pozidriv	4.5	35	11843189
Stainless steel	Pozidriv	4.5	40	11843190
Stainless steel	Pozidriv	4.5	45	11843191
Stainless steel	Pozidriv	4.5	50	11843192
Stainless steel	Pozidriv	4.5	60	11843193
Stainless steel	Pozidriv	4.5	70	11843194
Stainless steel	Pozidriv	5	30	11843195
Stainless steel	Pozidriv	5	40	11843197
Stainless steel	Pozidriv	5	70	11843201
Stainless steel	Pozidriv	5	80	11843202
Stainless steel	Pozidriv	6	40	11843203
Stainless steel	Pozidriv	6	50	11843204
Stainless steel	Pozidriv	6	70	11843206
Stainless steel	Pozidriv	6	80	11843207
Stainless steel	Pozidriv	6	90	11843208
Stainless steel	Pozidriv	6	100	11843209

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.