


HONEYWELL Pressure reducing valve Type 145 series D05FT brass external thread



Characteristics

Series: D05FT
Type: 145
Model: Direct-acting
Connection: External thread (BSPP)
Maximum inlet pressure: 16 bar
Medium temperature: 0 / 80 °C
Suitable for gases: 0
Housing material: Brass
Material quality: Dezincification resistant brass

Characteristics [2]

Material disc: Dezincification resistant brass
Seat material: Dezincification resistant brass
Membrane material: EPDM
Spring material: Spring steel
Material spring bonnet: Brass
With couplers: Yes
Backflow preventer: No

Nominal inner diameter	Capacity type	Kvs value m ³ /h	Reduced pressure range bar	Article
1/2" [15]	Standard	3	1.5 / 6	12160377
3/4" [20]	Standard	3.5	1.5 / 6	12160380
1" [25]	Standard	3.7	1.5 / 6	12160381
1.1/4" [32]	Standard	7.3	1.5 / 6	12160379
1.1/2" [40]	Standard	7.5	1.5 / 6	12160378
2" [50]	Standard	7.7	1.5 / 6	12160382

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.