



GF T-piece reducer 90° Series: 200 PVC-U Glued sleeve

Characteristics

Series: 200

Shape: T-piece reducer

Material: PVC-U

Connection: Glued sleeve

Angle of bow: 90 °

Material connection 2: PVC-U

Material connection 3: PVC-U

Minimum medium temperature (continuous): 0 °C

Maximum medium temperature (continuous): 60 °C

External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Article
mm	mm		
25	20	PN16	10046318
32	20	PN16	10046320
32	25	PN16	10046319
40	20	PN16	10046323
40	25	PN16	10046322
40	32	PN16	10046321
50	20	PN16	10046296
50	25	PN16	10046297
50	32	PN16	10046325
50	40	PN16	10046324
63	25	PN16	10046298
63	32	PN16	10046328
63	40	PN16	10046327
63	50	PN16	10046326
75	32	PN16	11076246
75	40	PN16	11285116
75	50	PN16	11098236
75	63	PN16	11181303
90	32	PN16	11095530
90	50	PN16	11095531
90	63	PN16	11076250
90	75	PN16	11095532
110	32	PN16	11076255
110	50	PN16	11076254
110	63	PN16	11417265
110	90	PN16	11084926
125	50	PN16	11245233
125	90	PN16	11076285
140	50	PN16	11202888
140	75	PN16	11458482
140	110	PN16	11285117
160	110	PN16	11111878
225	110	PN10	11285118
225	160	PN10	11285119
280	160	PN10	11170894
280	225	PN10	11285120
315	160	PN6	11285121
315	225	PN6	11285122

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.