




ASCO Pilot valve 3/2 fig. 33400NF series 327 brass explosion proof Ex-d



Characteristics

Series: 327
Type: 33400NF
Model: Pilot valve 3/2 way
Function: Universal
Actuation: Direct-acting
Including plug: Not applicable
Orifice: 5.7 mm
Kvs value: 0.45 m³/h
Max. viscosity: 65 mm²/s
Minimum pressure difference: 0 bar
Maximum pressure difference: 10 bar
Housing material: Brass
Sealing: FPM (FKM)
Material coil housing: Aluminium
Material shorting ring: Copper
Working time: 100 %



Characteristics [2]

Level of protection (IP value): IP66/IP67
Emergency manual operation: No
Explosion-proof: Yes
Ex-class: II 2G Ex db IIC Gb T6-T5-T4 / II 2D Ex tb IIIC Db
ATEX Zone: Zone 1 / 21
SIL certified: Yes
Approvals: ATEX IECEx, SIL
Medium temperature: From -20 °C to 120 °C

Process connection	Size process connection	Connection air exhaust(s)	Coil type	Supply voltage	Frequency	Electrical connection	Power	Starting power	Ambient temperature	Article
Internal thread (BSPP)	1/4" [8]	1/4" [8]	NF	24V DC		Cable box with 1/2" NPT cable entry	9 W [hot] - 11.2 W [cold]		From -60 °C to 40 °C	12427356
Internal thread (BSPP)	1/4" [8]	1/4" [8]	NFET	24V DC		Cable box with M20 x 1.5 cable entry	9 W [hot] - 11.2 W [cold]		From -60 °C to 40 °C	12427358
Internal thread (NPT)	1/4" [8]	1/4" [8]	NF	24V DC		Cable box with 1/2" NPT cable entry	3.2 W [hot] / 3.6 W [cold]		From -60 °C to 60 °C	13409870
Internal thread (NPT)	1/4" [8]	1/4" [8]	NFET	24V DC		Cable box with M20 x 1.5 cable entry	3.2 W [hot] / 3.6 W [cold]		From -60 °C to 60 °C	11815269
Internal thread (NPT)	1/4" [8]	1/4" [8]	NF	24V DC		Cable box with 1/2" NPT cable entry	9 W [hot] - 11.2 W [cold]		From -60 °C to 40 °C	11403743
Internal thread (NPT)	1/4" [8]	1/4" [8]	NF	230V AC	50/60Hz	Cable box with 1/2" NPT cable entry	10 W	10 VA	From -60 °C to 40 °C	13409871

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.