



## ECON® Pressure gauge valve Type 342 brass internal/external thread

### Characteristics


**Type:** 342

**Housing material:** Brass

**Operation:** Handle

### Application

- Recommended in: Utilities



| Process connection | Size process connection | Connection instrument side | Size instrument connection | Inspection connection | Pressure rating | Maximum pressure at 20 °C<br>bar | Maximum medium temperature (continuous)<br>°C | Primary spindle seal material | Spindle material | Article          |
|--------------------|-------------------------|----------------------------|----------------------------|-----------------------|-----------------|----------------------------------|---|-------------------------------|------------------|------------------|
| External thread    | 1/2" BSPP(G)            | Internal thread            | 1/2" BSPP(G)               | None                  | PN25            | 25                               | 50  | PTFE                          | Brass            | SY0034201/2-CAAC |
| External thread    | 3/8" BSPP(G)            | Internal thread            | 3/8" BSPP(G)               | None                  | PN25            | 16                               | 50  | PTFE                          | Brass            | SY0034203/8-CAAC |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.