

LEGRIS 1805 series stainless steel male stud coupling BSP tapered thread



Characteristics

Series: 1805

Material: Stainless steel 316L

Size table:

C	D mm	F mm	F1 mm	H mm	H1 mm
R1/4	6	14	13	19.5	7.5
R1/8	6	12	13	19.5	7.5
R1/8	8	13	14	21	7
R1/2	10	22	19	26.5	10
R1/4	10	17	19	25.5	9
R3/8	10	17	19	25.5	9
R1/2	12	22	22	27	10
R1/4	12	19	22	26	9
R3/8	12	19	22	26	9
R1/2	16	24	27	28.8	9.5
R3/8	16	24	27	28.5	9.5

Manufacturer ID	Connection 1	Connection 2	C	D mm	F mm	F1 mm	H mm	H1 mm	Article
1805 06 13	6 mm	1/4" BSPT(R)	R1/4	6	14	13	19.5	7.5	23213940
1805 06 10	6 mm	1/8" BSPT(R)	R1/8	6	12	13	19.5	7.5	23215618
1805 08 10	8 mm	1/8" BSPT(R)	R1/8	8	13	14	21	7	23215616
1805 10 21	10 mm	1/2" BSPT(R)	R1/2	10	22	19	26.5	10	23216235
1805 10 13	10 mm	1/4" BSPT(R)	R1/4	10	17	19	25.5	9	23215617
1805 10 17	10 mm	3/8" BSPT(R)	R3/8	10	17	19	25.5	9	23215621
1805 12 21	12 mm	1/2" BSPT(R)	R1/2	12	22	22	27	10	23216241
1805 12 13	12 mm	1/4" BSPT(R)	R1/4	12	19	22	26	9	23216237
1805 12 17	12 mm	3/8" BSPT(R)	R3/8	12	19	22	26	9	23216239
1805 16 21	16 mm	1/2" BSPT(R)	R1/2	16	24	27	28.8	9.5	23216245
1805 16 17	16 mm	3/8" BSPT(R)	R3/8	16	24	27	28.5	9.5	23216243

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.