



## GF 3-way coupling in PVDF Serie: 510 PN10 Plastic welded sleeve

### Characteristics

**Series:** 510

**Material:** PVDF

**Connection:** Plastic welded sleeve

**Suited for electrofusion fitting:** No

**Seal material:** FPM (FKM)

**Minimum medium temperature (continuous):** -20 °C

**Maximum medium temperature (continuous):** 140 °C

| Shape            | External tube diameter of connection<br>mm | Pressure rating | Article  |
|------------------|--------------------------------------------|-----------------|----------|
| 3-piece coupling | 16                                         | PN16            | 10044124 |
| 3-piece coupling | 20                                         | PN16            | 10044125 |
| 3-piece coupling | 25                                         | PN16            | 10044126 |
| 3-piece coupling | 32                                         | PN16            | 10044127 |
| 3-piece coupling | 40                                         | PN16            | 10044128 |
| 3-piece coupling | 50                                         | PN16            | 10044129 |
| 3-piece coupling | 63                                         | PN16            | 10044130 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.