



AKATHERM Bend 90° in PE-100 SDR11 Plastic welded end

Characteristics

Material: PE-100

Connection: Plastic welded end

Suited for electrofusion fitting: No

Angle of bow: 90 °

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 45 °C

Shape	External tube diameter of connection mm	Pressure rating	Article
Bend	20	PN16	10044606
Bend	25	PN16	10044607
Bend	32	PN16	10044608
Bend	40	PN16	10044609
Bend	50	PN16	10044610
Bend	63	PN16	10044611
Bend	75	PN16	10044612
Bend	90	PN16	10044613
Bend	110	PN16	10044614
Bend	125	PN16	10044615
Bend	140	PN16	10044616
Bend	160	PN16	10044617
Bend	200	PN16	10044619
Bend	225	PN16	10044620
Bend	250	PN16	10044621
Bend	280	PN16	10044622
Bend	315	PN16	10044623
Bend	355	PN16	10077825
Bend	400	PN16	11052912

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.