

GF Centric reducer PP-H Serie: 910 PN10



Characteristics

Series: 910

Centric: Yes

Material: PP-H

Connection: Plastic welded sleeve

Connection 2: Plastic welded end

Suited for electrofusion fitting: No

Minimum medium temperature (continuous): 0 °C

Maximum medium temperature (continuous): 80 °C

Shape	External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Article
	mm	mm		
Reduction piece	20	16	PN10	10044390
Reduction piece	25	16	PN10	10044392
Reduction piece	25	20	PN10	10044391
Reduction piece	32	25	PN10	10044393
Reduction piece	32	20	PN10	10044394
Reduction piece	40	20	PN10	10044397
Reduction piece	40	32	PN10	10044395
Reduction piece	40	25	PN10	10044396
Reduction piece	50	32	PN10	10044399
Reduction piece	50	25	PN10	10044400
Reduction piece	50	40	PN10	10044398
Reduction piece	50	20	PN10	10044401
Reduction piece	63	32	PN10	10044404
Reduction piece	63	50	PN10	10044402
Reduction piece	63	40	PN10	10044403
Reduction piece	75	63	PN10	10044917
Reduction piece	90	63	PN10	10044406
Reduction piece	90	75	PN10	10044918
Reduction piece	110	90	PN10	10044407

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.