



GF Centric reducer PE-80 Serie: 910 PN10

Characteristics

- Series:** 910
- Centric:** Yes
- Material:** PE-80
- Connection:** Plastic welded sleeve
- Connection 2:** Plastic welded sleeve
- Suited for electrofusion fitting:** No
- Minimum medium temperature (continuous):** -20 °C
- Maximum medium temperature (continuous):** 45 °C

Shape	External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Article
	mm	mm		
Reduction piece	25	20	PN10	10044425
Reduction piece	32	20	PN10	10044426
Reduction piece	40	25	PN10	10044428
Reduction piece	40	25	PN10	10044427
Reduction piece	40	20	PN10	11069485
Reduction piece	50	32	PN10	10044430
Reduction piece	50	32	PN10	10044429
Reduction piece	63	40	PN10	10044432
Reduction piece	63	20	PN10	11094430
Reduction piece	63	40	PN10	10044897
Reduction piece	63	25	PN10	11088139
Reduction piece	63	50	PN10	10044431
Reduction piece	75	63	PN10	10044898
Reduction piece	90	63	PN10	11323028
Reduction piece	90	75	PN10	10044899
Reduction piece	110	90	PN10	10044900

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.