



GF Socket with integrated clamping device in PE-100 Serie: 911 SDR11 - electro fusion

Characteristics

Series: 911

Material: PE-100

Connection: Electro welded sleeve

Suited for electrofusion fitting: No

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 45 °C

Shape	External tube diameter of connection mm	Pressure rating	Article
Electrofusion socket	20	PN16	11255747
Electrofusion socket	25	PN16	11266067
Electrofusion socket	32	PN16	11220746
Electrofusion socket	40	PN16	11220745
Electrofusion socket	50	PN16	11220744
Electrofusion socket	63	PN16	11220743
Electrofusion socket	75	PN16	11240435
Electrofusion socket	90	PN16	11220711
Electrofusion socket	110	PN16	11220710
Electrofusion socket	125	PN16	11220709
Electrofusion socket	140	PN16	11220235
Electrofusion socket	160	PN16	11248035
Electrofusion socket	180	PN16	11266068
Electrofusion socket	200	PN16	11248036
Electrofusion socket	225	PN16	11255581
Electrofusion socket	280	PN16	11266069
Electrofusion socket	315	PN16	11266070

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.