## GF Hose tail in PE-100 Serie: 968 SDR11



**Characteristics** 

Series: 968 Material: PE-100

Connection: Plastic welded end

Connection 2: Hose tail

Suited for electrofusion fitting: No

Minimum medium temperature (continuous):  $-20 \, ^{\circ}\text{C}$ Maximum medium temperature (continuous):  $45 \, ^{\circ}\text{C}$ 

| Shape     | External tube diameter of connection<br>mm | Pressure rating | Article  |
|-----------|--|-----------------|----------|
| Hose tail | 20   | PN16            | 11237204 |
| Hose tail | 25   | PN16            | 11940410 |
| Hose tail | 32   | PN16            | 11435187 |
| Hose tail | 40   | PN16            | 11350070 |
| Hose tail | 50   | PN16            | 11472980 |
| Hose tail | 63   | PN16            | 11559919 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

> ; PR\_EC010335\_0142\_FW\_EN\_29.06.2024