



GF Reducer in PE Serie: 908 SDR11

Characteristics

Series: 908

Material: PE-100

Connection: Plastic welded end

Suited for electrofusion fitting: No

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 45 °C

Shape	External tube diameter of connection mm	External tube diameter of connection 2 mm	Pressure rating	Article
Reduction piece	75	50	PN10	12451444
Reduction piece	140	110	PN16	12451363
Reduction piece	140	125	PN16	12451364
Reduction piece	160	110	PN16	12451365
Reduction piece	160	140	PN16	12451366
Reduction piece	180	140	PN16	12451369
Reduction piece	180	160	PN16	12451370
Reduction piece	180	110	PN16	12451368
Reduction piece	200	180	PN16	12451372
Reduction piece	200	160	PN16	12451371
Reduction piece	225	180	PN16	12451374
Reduction piece	225	160	PN16	12451373
Reduction piece	250	160	PN16	12451375
Reduction piece	250	225	PN16	12451376
Reduction piece	280	250	PN16	12451378
Reduction piece	280	225	PN16	12451377
Reduction piece	315	280	PN16	12451381
Reduction piece	315	250	PN16	12451380
Reduction piece	315	225	PN16	12451379

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.