



## GF Reducer in PE-100 Serie: 908 SDR17

### Characteristics

**Series:** 908

**Material:** PE-100

**Connection:** Plastic welded end

**Suited for electrofusion fitting:** No

**Minimum medium temperature (continuous):** -20 °C

**Maximum medium temperature (continuous):** 45 °C

Shape	External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Article
	mm	mm		
Reduction piece	25	20	PN16	11517253
Reduction piece	32	20	PN16	12451382
Reduction piece	32	25	PN16	11517241
Reduction piece	40	20	PN16	11611078
Reduction piece	50	32	PN16	12215757
Reduction piece	63	50	PN10	12120504
Reduction piece	63	32	PN16	11517240
Reduction piece	63	50	PN16	12133991
Reduction piece	75	40	PN16	12406923
Reduction piece	75	63	PN16	12188885
Reduction piece	75	50	PN16	12215758
Reduction piece	90	63	PN16	11335682
Reduction piece	90	75	PN16	12451385
Reduction piece	110	90	PN10	12120510
Reduction piece	110	75	PN16	12218601
Reduction piece	110		PN16	12134006
Reduction piece	125	110	PN16	12218600
Reduction piece	180	125	PN16	12177104
Reduction piece	225	200	PN16	12224599
Reduction piece	225	110	PN16	11055136

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.