

GF Reducer in PP Serie: 908 SDR11



Characteristics

Series: 908

Material: PP-H

Connection: Plastic welded end

Connection 2: Glued sleeve

Suited for electrofusion fitting: No

Minimum medium temperature (continuous): 0 °C

Maximum medium temperature (continuous): 80 °C

Shape	External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Article
	mm	mm		
Reduction piece	180	160	PN10	12451389
Reduction piece	180	125	PN10	12451388
Reduction piece	180	110	PN10	12451387
Reduction piece	200	180	PN10	12451391
Reduction piece	200	160	PN10	12451390
Reduction piece	225	180	PN10	12451393
Reduction piece	225	110	PN10	12451392
Reduction piece	225	200	PN10	12451394
Reduction piece	250	225	PN10	12451398
Reduction piece	250	160	PN10	12451395
Reduction piece	355	280	PN10	12451400
Reduction piece	355	250	PN10	12451399
Reduction piece	400	315	PN10	12451401

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.