

## GF Reducer in PP-H Serie: 908 SDR11/PN10



### Characteristics

**Series:** 908

**Material:** PP-H

**Connection:** Plastic welded end

**Connection 2:** Glued sleeve

**Suited for electrofusion fitting:** No

**Minimum medium temperature (continuous):** 0 °C

**Maximum medium temperature (continuous):** 80 °C

Shape	External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Article
	mm	mm		
Reduction piece	25	20	PN10	11318864
Reduction piece	32	20	PN10	11169094
Reduction piece	32	25	PN10	11353843
Reduction piece	40	20	PN10	11226441
Reduction piece	40	32	PN10	11439169
Reduction piece	40	25	PN10	12103373
Reduction piece	50	40	PN10	11299038
Reduction piece	50	25	PN10	11540226
Reduction piece	50	32	PN10	11546751
Reduction piece	63	50	PN10	11299037
Reduction piece	63	40	PN10	11290426
Reduction piece	63	32	PN10	11028280
Reduction piece	75	40	PN10	12451449
Reduction piece	75	50	PN10	12451450
Reduction piece	75	63	PN10	11690315
Reduction piece	90	75	PN10	12451451
Reduction piece	90	63	PN10	11313263
Reduction piece	110	75	PN10	11690311
Reduction piece	110	90	PN10	11056630
Reduction piece	140	125	PN10	11415758
Reduction piece	160	110	PN6	11455633
Reduction piece	160	140	PN10	11463921
Reduction piece	160	110	PN10	11381204
Reduction piece	180	140	PN10	12334134

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.