



AKATHERM T-piece reducer PE-100 Plastic welded end

Characteristics

Shape: T-piece reducer

Material: PE-100

Connection: Plastic welded end

Material connection 2: PE-100

Material connection 3: PE-100

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 80 °C

| External tube diameter of connection | External tube diameter of connection 2 | Pressure rating | Article |
|--------------------------------------|---|-----------------|----------|
| mm | mm | | |
| 90 | 32 | SDR 11 | 10077889 |
| 110 | 32 | SDR 11 | 11060618 |
| 125 | 63 | SDR 11 | 11060619 |
| 140 | 63 | SDR 17 | 11060577 |
| 140 | 75 | SDR 11 | 11060620 |
| 140 | 75 | SDR 17 | 11060581 |
| 140 | 90 | SDR 11 | 11060621 |
| 140 | 90 | SDR 17 | 11060582 |
| 180 | 63 | SDR 11 | 11060624 |
| 180 | 63 | SDR 17 | 11060606 |
| 180 | 75 | SDR 11 | 11060625 |
| 180 | 75 | SDR 17 | 11060608 |
| 225 | 90 | SDR 11 | 11060631 |
| 225 | 125 | SDR 17 | 11060614 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.