



LINK-SEAL Link seal Series: C EPDM Steel galvanised

Link-Seal wall pass - Standard (Performance electrically insulating). Temperature resistance: -40 ° C to +80° C.

Link: EPDM rubber, general purpose water, air and humid environment. Bolts and nuts zinc plated quality DIN933/934 8.8.

Pressure plate: 30% PA-reinforced fiberglass for electrical insulation and the cathodic protection 6.6. Rubber color: black.

Features:

- Quick and easy assembly
- Safe and long life
- Resistant to heat, it can even be fireproof

Advantages:

- Saves time when by installation
- Absorbs noise and shock
- Close perfectly, even with off-center wall penetrations
- Easily removable

Fields of application:

- Pipi-lines
- Industry
- Chemistry
- Storage companies
- Hospitals
- Water Treatment
- Pools

Characteristics

Series: C

Material: EPDM

Airtight: Yes

Watertight: Yes

Stench-tight: Yes

Sound-absorbing: Yes

Material bolts and nuts: Steel galvanised

Minimum medium temperature (continuous): -40 °C

Maximum medium temperature (continuous): 120 °C

Type wall seal	Wall/partition/floor thickness mm	Colour	Article
LS 200 C	75	Black	10049123
LS 265-C	75	Black	12085742
LS 275-C	75	Black	10049125
LS 300-C	100	Black	10049127
LS 310-C	100	Black	12085748
LS 315-C	100	Black	10049129
LS 325-C	120	Black	10049131

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type wall seal	Wall/partition/floor thickness mm	Colour	Article
LS 340-C	120	Black	11267875
LS 360 C	120	Black	11284931
LS 400 C	140	Black	10049133
LS 410 C	140	Black	11284932
LS 425 C	140	Black	10049135
LS 440-C	140	Black	11426170
LS 475 C	140	Black	10049137
LS 500 C	150	Black	10049122
LS 525 C	150	Black	10049154
LS 575 C	150	Black	11047825
LS 615-C	150	Black	11401915
LS 650-C	150	Black	11955823

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.