



LINK-SEAL Link seal Series: OS NBR Stainless steel 316 (V4A)

Link-Seal wall pass - Corrosion resistant (performance electrical insulation). Temperature resistance: -40 ° C to +70° C.

Link: NBR rubber, resistant to oil, grease, aromatic hydrocarbons, solvents and oil-based media. Bolts and nuts grade AISI316.

Pressure plate: PA 6.6 reinforced with 30% glass fiber for electrical insulation and cathodic protection. Rubber color: green.

Features:

- Quick and easy assembly
- Safe and long life
- Resistant to heat, it can even be fireproof

Advantages:

- Saves time when by installation
- Absorbs noise and shock
- Close perfectly, even with off-center wall penetrations
- Easily removable

Fields of application:

- Pipi-lines
- Industry
- Chemistry
- Storage companies
- Hospitals
- Water Treatment
- Pools

Characteristics

Series: OS

Material: NBR

Airtight: Yes

Watertight: Yes

Stench-tight: Yes

Sound-absorbing: Yes

Material bolts and nuts: Stainless steel 316 (V4A)

Minimum medium temperature (continuous): -40 °C

Maximum medium temperature (continuous): 100 °C

Type wall seal	Wall/partition/floor thickness mm	Colour	Article
LS 200-OS-316	75	Green	11185523
LS 275-OS-316	75	Green	11537871
LS 300 OS-316	100	Green	11042375
LS 315 OS-316	100	Green	11625101
LS 325-OS-316	120	Green	11295159
LS 340 OS-316	120	Green	11554737
LS 360-OS-316	120	Green	12304381

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type wall seal	Wall/partition/floor thickness mm	Colour	Article
LS 400 OS-316	140	Green	11051985
LS 410 OS-316	140	Green	11665996
LS 425 OS-316	140	Green	11119980
LS 440-OS-316	140	Green	12561240
LS 500-OS-316	150	Green	11554436
LS 525-OS-316	150	Green	11652138
LS 575-OS-316	150	Green	12554324
LS 615-OS-316	150	Green	12554325
LS 650-OS-316	150	Green	12554326

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.