



LINK-SEAL Link seal Series: S EPDM Stainless steel 316 (V4A)

Link-Seal wall pass - Corrosion resistant (performance electrical insulation). Temperature resistance: -40 ° C to +80° C.

Link: EPDM rubber used in the chemical treatment companies, water, food and paper, water and waste. Bolts and nuts grade AISI316.

Pressure plate: PA 6.6 reinforced with 30% glass fiber for electrical insulation and cathodic protection. Rubber color: black.

Features:

- Quick and easy assembly
- Safe and long life
- Resistant to heat, it can even be fireproof

Advantages:

- Saves time when by installation
- Absorbs noise and shock
- Close perfectly, even with off-center wall penetrations
- Easily removable

Fields of application:

- Pipi-lines
- Industry
- Chemistry
- Storage companies
- Hospitals
- Water Treatment
- Pools

Characteristics

Series: S

Material: EPDM

Airtight: Yes

Watertight: Yes

Stench-tight: Yes

Sound-absorbing: Yes

Material bolts and nuts: Stainless steel 316 (V4A)

Minimum medium temperature (continuous): -40 °C

Maximum medium temperature (continuous): 120 °C

Type wall seal	Wall/partition/floor thickness mm	Colour	Article
LS 200 S-316	75	Black	10049141
LS 265 S-316	75	Black	11448512
LS 275-S-316	75	Black	11049744
LS 300 S-316	100	Black	10049143
LS 310 S-316	100	Black	11444918
LS 315 S-316	100	Black	11046481
LS 325 S-316	120	Black	10049145

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type wall seal	Wall/partition/floor thickness mm	Colour	Article
LS 340 S-316	120	Black	11284928
LS 360 S-316	120	Black	11284929
LS 400 S-316	140	Black	10049147
LS 410 S-316	140	Black	11284930
LS 425 S-316	140	Black	10049149
LS 440 S-316	140	Black	12085751
LS 475 S-316	140	Black	10049152
LS 500 S-316	150	Black	11155435
LS 525 S-316	150	Black	11140476
LS 575 S-316	150	Black	11089899
LS 615 S-316	150	Black	11378044
LS 650 S-316	150	Black	11486314

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.