

FREUDENBERG U-cup type NA150




Characteristics

Type: NA150

Principle of operation: Single acting

Max. operating pressure: 100 bar

Maximum speed: 0.5 m/s



Bore diameter	Groove diameter	Groove width	Seal height	Material seal	Compound	Temperature range	Article
mm	mm	mm	mm			°C	
12	6	4.5	4	NBR	80 NBR 878	-30 / 100	11312826
16	10	4.5	4	NBR	80 NBR 878	-30 / 100	11312033
20	12	6	5.5	NBR	80 NBR 878	-30 / 100	11953803
25	17	6	5.5	NBR	80 NBR 878	-30 / 100	11292742
32	24	6	5.5	NBR	80 NBR 878	-30 / 100	11292741
40	30	7.5	7	NBR	80 NBR 878	-30 / 100	11059018
50	40	7.5	7	NBR	80 NBR 878	-30 / 100	11292740
63	53	7.5	7	NBR	80 NBR 878	-30 / 100	11268488
70	58	9.5	8.5	NBR	80 NBR 878	-30 / 100	11309077
80	68	9.5	8.5	NBR	80 NBR 878	-30 / 100	11104972
100	88	9.5	8.5	NBR	80 NBR 878	-30 / 100	11292739
125	110	11	10	NBR	80 NBR 878	-30 / 100	11480531
140	125	11	10	NBR	80 NBR 878	-30 / 100	11902423
160	145	11	10	NBR	80 NBR 878	-30 / 100	11292738
180	160	15	14	NBR	80 NBR 878	-30 / 100	11292737
200	180	15	14	NBR	80 NBR 878	-30 / 100	11461348

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.